

Candle

- Radiate a clear, white light that features a brilliant sparkle effect
- Provide consistent color from every angle
- E12 socket
- 120V input
- CRI ≥80
- 3 years warranty



| P/N | Wattage (W) | Lumen (lm) | Efficacy (lm/W) | Beam Angle |
|---------------------|-------------|------------|-----------------|------------|
| ABL-CANW-06E2R-A-LD | 5 | 325 | 70 | 40° |
| ABL-CANW-06E2F-A-LD | 5 | 325 | 90 | 25° |

MR16

- Suitable for accent, architectural, hospitality, and recessed lighting
- CRI ≥80
- 3 years warranty
- GU5.3 socket with 12V input
- GU10 socket with 120V input



| GU5.3 P/N | Wattage (W) | Lumen (lm) | Efficacy (lm/W) | Beam Angle |
|---------------------|-------------|------------|-----------------|------------|
| ABL-M16W-07G5W-A-LD | 7 | 400 | 60 | 40° |
| ABL-M16W-07G5N-A-LD | 7 | 400 | 60 | 25° |



| GU10 P/N | Wattage (W) | Lumen (lm) | Efficacy (lm/W) | Beam Angle |
|---------------------|-------------|------------|-----------------|------------|
| ABL-M16W-07G1W-A-LD | 7 | 450 | 65 | 40° |
| ABL-M16W-07G1N-A-LD | 7 | 450 | 65 | 25° |

LIGHTING BEYOND ILLUMINATION



AmericanBright™
Bright ideas. Brilliant solutions.

13815-C Magnolia Ave, Chino, CA 91710
Website: www.ab-lighting.com
Email: info@ab-lighting.com
Tel: 866.533.5588 | Fax: 909.628.5006



AmericanBright™
Bright ideas. Brilliant solutions.

| E SERIES |



LED REPLACEMENT LAMPS FOR Commercial | Residential



Bright ideas. Brilliant solutions.

IngeniLED™ E series replacement lamps are designed for retail, office and home lightings. They have the aesthetic and practical qualities of conventional lamps, as well as being more energy efficient and having long life spans. With LED technology, there is no hazardous material or UV emission and help protect the environment by reducing the total carbon footprint.



A19

- Omnidirectional light output
- E26 socket
- 120V input
- CRI ≥80
- 25,000 hrs warranty



| P/N | Wattage (W) | Lumen (lm) | Efficacy (lm/W) | Beam Angle |
|---------------------|-------------|------------|-----------------|------------|
| ABL-A19W-07E6W-A-LD | 7 | 450 | 70 | 300° |
| ABL-A19W-09E6W-A-LD | 9 | 800 | 90 | 300° |



| P/N | Wattage (W) | Lumen (lm) | Efficacy (lm/W) | Beam Angle |
|---------------------|-------------|------------|-----------------|------------|
| ABL-A19W-07E6W-A-LN | 7 | 450 | 70 | 300° |
| ABL-A19W-09E6W-A-LN | 9 | 800 | 90 | 300° |

PAR

- Narrow beam angle for precise light projection
- E26/E27 socket
- 120V input
- CRI ≥80
- 3 years warranty



| P/N | Wattage (W) | Lumen (lm) | Efficacy (lm/W) | Beam Angle |
|---------------------|-------------|------------|-----------------|------------|
| ABL-P38W-15E6W-A-LD | 15 | 1050 | 70 | 40° |
| ABL-P30W-12E6W-A-LD | 12 | 850 | 70 | 40° |
| ABL-P20W-07E6W-A-LD | 7 | 470 | 70 | 40° |

BR

- BR lens conceals LEDs from view and evenly distributes light
- E26/E27 socket
- 120V input
- CRI ≥80
- 3 years warranty



| P/N | Wattage (W) | Lumen (lm) | Efficacy (lm/W) | Beam Angle |
|---------------------|-------------|------------|-----------------|------------|
| ABL-B40W-17E6W-A-LD | 17 | 1400 | 82 | 40° |
| ABL-B30W-11E6W-A-LD | 11 | 750 | 70 | 40° |
| ABL-B20W-07E6W-A-LD | 7 | 500 | 70 | 40° |